



UT33D+ Palm Size Multimeter



The new generation UT33+ series redefines the performance standards for entry-level digital multimeters. Our innovative industrial design ensures that these products can withstand 2 meters drop. The new LCD display layout provides a better user experience. This series ensures that users can work safely in CAT II 600V environment. Special features are, 2mF capacitance test (UT33A+); battery test (UT33B+); temperature measurement function (UT33C+); non-contact voltage (NCV) test (UT33D+).

Features:

1. Clear LCD display
2. Comfortable protective cover, with test lead hanging groove
3. 2 meters drop test, precision protection
4. Loud buzzer sound; Ergonomic design



Specifications	Range	UT33D+
DC voltage (V)	200mV/2V/20V/200V/600V	±(0.5%+2)
AC voltage (V)	200V/600V	±(1.2%+3)
DC current (A)	2000µA/20mA/200mA/10A	±(1%+2)
Resistance (Ω)	200Ω/2kΩ/20kΩ /200kΩ/20MΩ/200MΩ	±(0.8%+2)
Features		
Display count		2000
Auto power off/Auto backlight off		√
Diode test/Continuity buzzer		√
2m drop test/ Test probe holder		√
Range selection		Manual
NCV		√
General Characteristics		
Power	1.5V battery (R03) x 2	
Display	66mm x 51mm	
Product net weight	Red and grey	
Product color	206g (batteries included)	
Product size	134mm x 77mm x 47mm	
Standard accessories	Batteries, test leads	